

## Specifications



### REFRACTIVE POWER MEASUREMENT

Spherical power	-30.00 D to +25.00 D (at VD = 12.00 mm)
Cylindrical power	0.00 D to ± 12.50 D (at VD = 12.00 mm)
Astigmatic axis	0° to 180°
Minimum pupil diameter	2.0 mm

### KERATOMETRY MEASUREMENT

Corneal curvature radius	5.00 mm to 13.00 mm
Corneal astigmatic axis	0° to 180°

### INTRAOCULAR PRESSURE MEASUREMENT

Measurement range	1 mm Hg to 60 mm Hg (1 hPa to 80 hPa)
-------------------	---------------------------------------

### PACHYMETRY MEASUREMENT

Measurement range	300 µm to 800 µm
-------------------	------------------

### TOPOGRAPHY MEASUREMENT

Corneal curvature radius	5.50 mm to 10.00 mm
Corneal astigmatic axis	0° to 180°

### AUXILIARY FUNCTION

Interpupillary distance	20 mm to 85 mm
Corneal diameter and pupil diameter	1.00 mm to 14.00 mm
Dry-eye application	Blinking frequency, tear meniscus height, hyperemia, Meibomian glands

### DATA MANAGEMENT

Internal database	Integrated SD card
Printer	Integrated thermal printer
Data output type	3x USB 2.0, 1x Ethernet, 1x SD card slot, 1x WLAN (not available in all countries)
Export format	DCM, XML, CSV, JPG, PDF

### DIMENSIONS AND ELECTRICAL REQUIREMENTS

Dimensions WDH	312 x 491 x 450 mm
Weight	approx. 23 kg
Voltage	100 VAC to 240 VAC
Frequency	50/60 Hz
Power consumption	110 VA
Laser class	Class 1

TOMEY EUROPE  
TOMEY GMBH

Wiesbadener Strasse 21  
90427 Nuremberg | Germany  
+49 911 938 546 2 - 0  
+49 911 938 546 2 - 20  
info@tomey.de

tomey.de

Follow TOMEY



TOMEY GmbH is the European headquarters of TOMEY Corporation, 2-11-33 Noritakeshimachi Nishi-Ku, Nagoya, 451-0051, Japan



2023.05 - subject to change without notice

## Simplicity meets variety

The versatile multifunctional unit for eye examinations can:

- + Determine the objective refraction
- + Visualise the corneal shape
- + Assess the IOP and C.IOP as part of glaucoma screening
- + Measure the central corneal thickness
- + Observe dry-eye

# MR-6000

## Multifunction Unit

**You + eye.**  
We care.

# MR-6000 Multifunction Unit

The MR-6000 delivers a smart combination of five different eye examinations and a Dry Eye observation app. Along with the advantage of automatic alignment, this means that the MR-6000 speeds up your workflow and makes it more efficient.



**Dry-eye application**  
Blinking frequency, tear meniscus height, hyperemia, and Meibomian gland observation all help assess dry eye.



**Topography**  
16 Mire rings examine an area 8 mm in diameter. A number of topography maps, including Fourier analysis, provide a wide range of options for visualising corneal shape.

**Wide range alignment by image recognition**  
Refined auto alignment and auto shot support the operator during the examination.

**Measurement cone interchange in just 4 sec**  
Electrical cone interchange enables rapid switching between the measurement modes.

**Pupil and corneal diameter**  
The diameters of pupil and cornea (WTW) are measured with each topography. Manual correction allows the user to adjust the measurement points.

**Five functions in one system**  
This multifunction unit includes objective refraction, keratometry, topography, tonometry, and pachymetry. In addition, the Dry Eye observation app completes the powerful 5 + 1 system.

**Quick refraction mode**  
The quick refraction mode supports refraction values to be obtained within seconds despite fixation loss: for example, for patients with nystagmus, children, or uncooperative patients.

**Corrected IOP**  
A new generation of air-flow technology delivers a patient-friendly and gentle air puff. The automated IOP correction mode utilizes pachymetry values to correct the IOP.



"IT'S APPEALING TO WORK WITH HIGH-END TECHNOLOGY DEVICES AND LEARN ABOUT THEIR BENEFITS FOR MEDICAL TREATMENT."

*Katharina Koriski*

TECHNICAL DEPARTMENT  
ENGINEER

